COLOUR ECOTANK PRINTER L3250



AN ECO-NOMICAL AND ECO-FRIENDLY, ALL-IN-ONE PRINTER FOR HOME USE WITH WIRELESS PRINTING CAPABILITY

EPSON

The EcoTank L3250 multi-function printer is designed for printing with true convenience at home. A cost-per-print of just 9 Paise (black)* and 24 Paise (colour)* brings savings in every print. One can expect a high print yield of up to 4,500 pages for black, and 7,500 pages for colour - for non-stop printing. It can even print borderless photos - up to 4R in size. The integrated ink tanks and designated nozzles ensure spill-free and error-free refilling. Wireless connectivity enables printing from smart devices. Epson's Heat-Free Technology helps keep power consumption to a minimum, giving it the capability to print even on a UPS. The Epson Smart Panel app can be downloaded on mobile to manage the printer's functions and setup with ease.







Low Cost, High Yield

Non-stop printing with affordable, spill-free refill ink bottles. Savings every time with prints at 9 Paise (black)* and 24 Paise (colour).* **Borderless Printing**

Professional quality, borderless photo printing in sizes up to 4R.

Epson Smart Panel

Download the Epson Smart Panel app to mobile devices for direct access to functions such as print, scan and copy while monitoring the printer's operation.

For cost-per-print calculations, visit epson.co.in/parameters. *Source: IDC Asia Pacific Hardcopy Peripheral Tracker FY2022 01. Volume market share of A4 Inkjet printers and MFPs.

SPECIFICATIONS ECOTANK L3250



| IODEL NUMBER | L3250 |
|--|---|
| Printer | |
| rinter Type | Print, Scan & Copy |
| rinting | |
| rinting rinting Technology | Piezoelectric Printhead |
| | 180 x 1 nozzles Black, 59 x 1 nozzles per Colour (Cyan, Magenta, Yellow) |
| lozzle Configuration | |
| flaximum Resolution | 5760 x 1440 dpi |
| rint Speed*1 | |
| raft Text - Memo, A4 (Black#1 / Colour#2) | Up to 33.0 ppm / 15.0 ppm |
| O 24734, A4 (Black / Colour) | Up to 10.0 ipm / 5.0 ipm |
| rst Page Out Time (Black / Colour) | Approx. 10 sec / 16 sec |
| hoto Default - 10 x 15 cm / 4 x 6"*2 #3 | |
| Border / Borderless | Approx. 69 sec per photo (Border) / 90 sec per photo (Borderless) |
| inter Language | ESC/P-R, ESC/P Raster |
| opying | |
| opy Speed | |
| O 29183, A4 (Black / Colour) | Up to 7.7 ipm / 3.8 ipm |
| aximum Copies from Standalone | 20 copies |
| aximum Copy Resolution | 600 x 600 dpi |
| aximum Copy Size | A4, LTR |
| canning | |
| canner Type | Flatbed colour image scanner |
| ensor Type | CIS |
| ptical Resolution | 1200 x 2400 dpi |
| aximum Scan Area | 216 x 297 mm |
| canner BIT Depth | |
| - | 48-bit input, 24-bit output |
| olour | |
| irayscale | 16-bit input, 8-bit output |
| lack and White | 16-bit input, 1-bit output |
| can Speed | |
| lonochrome 200 dpi | Up to 11 sec |
| olour 200 dpi | Up to 28 sec |
| aper Handling | |
| umber of Paper Trays | 1 |
| aper Hold Capacity | |
| put Capacity | Up to 100 sheets of Plain Paper (80 g/m²) Up to 20 sheets of Premium Glossy Photo Paper |
| utput Capacity | Up to 30 sheets of Plain Paper (80 g/m ²) Up to 20 sheets of Premium Glossy Photo PaperPaper |
| aper Size | Legal (8.5 x 14"), Indian-Legal (215 x 345 mm), 8.5 x 13", Letter, A4, 16K (195 x 270 mm), B5, A5, B6, A6, Hagaki (100 x |
| | 148 mm), 5 x 7", 5 x 8", 4 x 6", Envelopes: #10, DL, C6 |
| laximum Paper Size | 215.9 x 1200 mm |
| rint Margin | 0 mm top, left, right, bottom via custom settings in printer driver*3 |
| terface | |
| SB | USB 2.0 |
| etwork | Wi-Fi, Wi-Fi Direct |
| etwork Protocol | TCP/IPv4, TCP/IPv6 |
| etwork Management Protocols | SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD |
| obile/Software and Cloud Printing | |
| oson Connect | Encon iDrint Encon Email Drint Remote Drint Driver |
| | Epson iPrint, Epson Email Print, Remote Print Driver |
| | Epson Smart Panel |
| | Encon Coop@mort |
| oftware | Epson ScanSmart |
| oftware | |
| oftware | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.6 |
| oftware rinter Software perating System Compatibility | |
| oftware inter Software perating System Compatibility ectrical Specifications | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later |
| oftware rinter Software perating System Compatibility ectrical Specifications ated Voltage | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V |
| oftware inter Software berating System Compatibility ectrical Specifications ated Voltage ated Frequency | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later |
| httware inter Software berating System Compatibility ectrical Specifications ated Voltage ted Frequency over Consumption | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz |
| ftware inter Software inter Software certical Specifications ted Voltage ted Frequency wer Consumption berating | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W |
| htware inter Software berating System Compatibility ectrical Specifications ted Voltage ted Frequency wer Consumption berating | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W |
| ftware inter Software inter Software control System Compatibility extrical Specifications ted Voltage ted Frequency wer Consumption errating andby | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W |
| ftware inter Software everating System Compatibility extrical Specifications ted Voltage ted Frequency wer Consumption verating andby sep | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W |
| httware inter Software berating System Compatibility ectrical Specifications ated Voltage ated Voltage ted Frequency ower Consumption berating andby sep ower Off | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W 0.7 W |
| httware inter Software berating System Compatibility ectrical Specifications tated Voltage tated Frequency were Consumption berating andby seep were Off bise Level | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 Or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W 0.7 W 0.2 W |
| oftware inter Software berating System Compatibility ectrical Specifications ated Voltage ated Frequency wer Consumption berating andby eep bwer Off c) Frinting / Premium Glossy Photo Paper | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W 0.7 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.2 B(A), |
| oftware inter Software perating System Compatibility ectrical Specifications ated Voltage ated Frequency ower Consumption perating andby eep power Off poise Level C Printing / Premium Glossy Photo Paper ast Photo | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W 0.7 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.2 B(A), Sound Pressure (Black / Colour) 38 / 39 dB(A) |
| oftware inter Software perating System Compatibility lectrical Specifications ated Voltage ated Voltage ated Frequency ower Consumption perating aradby eep ower Off oise Level C Printing / Premium Glossy Photo Paper sit Photo C Printing / Plain Paper Default*4 | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W 0.7 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.2 B(A), Sound Pressure (Black / Colour) 6.4 / 6.2 B(A), Sound Pressure (Black / Colour) 50 / 48 dB(A) |
| oftware inter Software berating System Compatibility ectrical Specifications ated Voltage ated Frequency wer Consumption berating andby eep wer Off bise Level C Printing / Premium Glossy Photo Paper ast Photo 2 Printing / Plain Paper Default*4 bonsumables | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W 0.7 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.2 B(A), Sound Pressure (Black / Colour) 38 / 39 dB(A) Sound Power (Black / Colour) 6.4 / 6.2 B(A), Sound Pressure (Black / Colour) 50 / 48 dB(A) Page Yield*5 Order Code |
| est Photo <u>C Printing / Plain Paper Default*4</u> onsumables lack Ink Bottle | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 Or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W 0.7 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.2 B(A), Sound Pressure (Black / Colour) 5.1 / 5.2 B(A), Sound Power (Black / Colour) 6.4 / 6.2 B(A), Sound Pressure (Black / Colour) 50 / 48 dB(A) Page Yield*5 Order Code 4,500 |
| oftware rinter Software perating System Compatibility lectrical Specifications ated Voltage ated Frequency ower Consumption perating tandby eep ower Off oise Level C Printing / Premium Glossy Photo Paper est Photo C Printing / Plain Paper Default*4 onsumables ack Ink Bottle yan Ink Bottle | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W 0.7 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.2 B(A), Sound Pressure (Black / Colour) 6.4 / 6.2 B(A), Sound Pressure (Black / Colour) 50 / 48 dB(A) Page Yield** 0.7 ISOU Colour) 0.7 ISOU Power (Black / Colour) 5.1 / 5.2 B(A), |
| oftware inter Software berating System Compatibility ectrical Specifications ated Voltage ated Voltage ated Frequency bower Consumption berating andby eep bower Off Dise Level C Printing / Premium Glossy Photo Paper sis Photo C Printing / Plain Paper Default*4 onsumables ack Ink Bottle agenta Ink Bottle | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W 0.7 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.2 B(A), Sound Pressure (Black / Colour) 6.4 / 6.2 B(A), Sound Pressure (Black / Colour) 50 / 48 dB(A) Page Yield*5 Order Code 4,500 C 13T00V198 C 13T00V298 7,500 (Composite Yield) |
| oftware inter Software berating System Compatibility ectrical Specifications ated Voltage ated Frequency wer Consumption berating andby eep bwer Off bise Level C Printing / Premium Glossy Photo Paper set Photo C Printing / Plain Paper Default* ⁴ bonsumables ack Ink Bottle yan Ink Bottle | Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10Windows Server 2003 / 2008 / 2012 / 2016 / 2019Mac OS X 10.6.8 or later AC 220-240 V 50-60 Hz 12.0 W 4.5 W 0.7 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.2 B(A), Sound Pressure (Black / Colour) 6.4 / 6.2 B(A), Sound Pressure (Black / Colour) 50 / 48 dB(A) Page Yield** 0.7 ISOU Colour) 0.7 ISOU Power (Black / Colour) 5.1 / 5.2 B(A), |

Dimensions & Weight

EcoTank L3250 Weight: 3.9 kg



Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.



*2 When printed on Epson Premium Glossy Photo Paper

- 3 Borderless printing is supported up to 4R (4 x 6"), otherwise 3 mm top, left, right, bottom.
- *4 Default mode in accordance with IS07779 for MFPs.
- *5 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and colour graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so yields could be lower than those of replacement ink bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour. Ink is used for both printing and printhead maintenance. All inks are used for both black and colour printing.

© 2022 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED VOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc.,registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc

Information correct at time of printing. Printed January 2023.

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-4566 5000 | Fax: 080-4566 5005

e-Waste to e-Clean



Regional Offices: Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Ernakulam - 4012 315, Coimbatore - 98942 19200, Kolkata - 4603 4729, Mumbai - 3079 8200, New Delhi - 4107 3101, Pune - 3028 6000/05, Hyderabad - 4857 0032, Jaipur - 0141 4923119

Epson Helpline: For product info or service- 1800 425 0011 For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat) Email: think@eid.epson.co.in